



PRODUCT DATA SHEET

SASOLWAX 3971

Revision: 26.02.2007

Property	Method	Unit	Specification
Dropping point	Mettler 1K/min	°C	78,0 - 84,0
Oil content	ASTM D 721	%	0,00 - 2,00
Needle penetration at 25°C	ASTM D 1321	1/10mm	25 - 33
Colour Saybolt	ASTM D 156	-	26 - 30
Kin. viscosity at 100°C	ASTM D 445	mm ² /s	12,0 - 16,0

pass

The product complies with the requirements of the 21 Code of Federal Regulations §172.886 (FDA)

NOTICE: This product information is indicative and does not include any guarantee.

Sasol Wax GmbH

Worthdamm 13-27, 20457 Hamburg, Postanschrift: Postfach 11 02 49, 20402 Hamburg
Telefon: +49 40 78115-0 Telefax: +49 40 78115-777 wax@de.sasol.com www.sasolwax.com

Geschäftsführung: Helmuth Schulze-Trautmann, William Anthony Cook Vorsitzender des Aufsichtsrats: Deodatus Schrenk
Registergericht Hamburg: HRB 73963 USt-IdNr./VAT No.: DE 118 922 039 Steuer-Nr./Tax-No. 27/164/00096

