

EGGAR&CO(Chemicals)Ltd

High Street
Theale
Reading
RG7 5AR



Tel: 0118 930 2379 Fax: 0118 932 3224
Email: sales@eggar.co.uk Web: www.eggar.co.uk

13i

Technical Specification**LOW CONTRACTION CONTAINER FILLING WAX 6214****Applications:**

Moulding paraffin wax for glass jars and similar container containers.

Quality characteristics:

Type 6214 is suitable for moulding, based on low melting paraffin waxes. It has been especially developed for the use in glass jars and similar containers for "one fill" operations. Owing to the improved low contraction a good optical appearance and a smooth surface may be achieved. The low melting point ensures that the wax burns down completely in the containers.

The wax composition shows excellent fragrance retention

Physical Data:

Congealing Point, °C	DIN-ISO 2207	48 - 52
Penetration at 25°C, dmm	DIN 51579	50 - 70
Viscosity at 100 °C, mm ² /sec	DIN 51562	4 - 6
Form	-	Slabs
Colour - solid state	Visual	Whitish

Technical advice: Attention should be paid to the low melting point when storing or shipping and during display.

For and on behalf of EGGAR & Co (Chemicals) Limited

This certificate has been generated electronically and is valid unsigned

John Gibbins (Director)

Issued:- 16 April 2008

Every care has been taken to compile this information accurately. In view of the fact that the application of this information is outside our control, we disclaim any liability incurred in connection with its application or use.