



High Street  
Theale

Reading  
RG7 5AR

Tel: 0118 930 2379 Fax: 0118 932 3224  
Email: sales@eggar.co.uk Web: www.eggar.co.uk

13i

## Technical Specification

### CA-398-10

#### A. GENERAL

- A-1. This specification describes one type of "EASTMAN" Cellulose Acetate filtered powder which is used in applications related to the coatings, photographic film, plastic, or membrane fields and must meet each of the requirements listed in Section B when tested as directed by the referenced methods.
- A-2. Material Safety Data Sheet 100000477 outlines the safety precautions for "EASTMAN" Cellulose Acetate.

#### B. PROPERTIES AND TEST METHODS

Properties	Limits	Test Methods
B-1. ASTM-A Viscosity, sec	8.0 - 13.0	TECE-A-CL-G-V-3
B-2. Acetyl by Titration, wt%	39.3 - 40.3	TECE-A-CL-G-POT-60
B-3. Dryer Moisture, wt%	3.0 (max)	TECE-A-CL-G-GA-8

For and on behalf of EGGAR & Co (Chemicals) Limited  
This certificate has been generated electronically and is valid unsigned  
John Gibbins (Director)

Issued:- 16 April 2008

Every care has been taken to compile this information accurately. In view of the fact that the application of this information is outside our control, we disclaim any liability incurred in connection with its application or use.