

EGGAR&CO(Chemicals)**Ltd**

High Street
Theale
Reading
RG7 5AR



Tel: 0118 930 2379 Fax: 0118 932 3224
Email: sales@eggar.co.uk Web: www.eggar.co.uk

13i

Technical Specification**CAP - 482-20****A. GENERAL**

- A-1. This specification describes one type of 'EASTMAN' Cellulose Acetate Propionate filtered powder, which must meet all of the requirements listed in Section B when tested as directed by the referenced methods.
- A-2. Material Safety Data Sheet MSDSGB/EURO/EN/150000001224 outlines the safety precautions for 'EASTMAN' Cellulose Acetate Propionate.

B. PROPERTIES AND TEST METHODS

Properties	Limits	Test Methods
B-1. ASTM-A Viscosity, secs	15 - 25	TECE-A-CL-G-V-23
B-2. Acetyl by GC, wt%	2.5 (max.)	TECE-A-CL-G-GC-29
B-3. Propionyl by GC, wt%	45 - 49	TECE-A-CL-G-GC-29
B-4 Free Acidity, ppm	300 (max.)	TECE-A-CL-G-IC-5
B-5. Moisture, wt%	3.0 (max.)	TECE-A-CL-G-GA-55

For and on behalf of EGGAR & Co (Chemicals) Limited
This certificate has been generated electronically and is valid unsigned
John Gibbins (Director)

Issued:- 16 April 2008

Every care has been taken to compile this information accurately. In view of the fact that the application of this information is outside our control, we disclaim any liability incurred in connection with its application or use.