

EASTMAN

SALES SPECIFICATION

FOR EASTMAN EAA (Ethyl Acetoacetate)	SPECIFICATION NO.	215-11
	NUMBER OF PAGES	1
	EFFECTIVE DATE	March 1998
	REVIEW DATE	11 January 2005

A. GENERAL

- A-1. This specification has been reviewed and replaces Sales Specification 215-10.
- A-2. This specification describes a grade of **EASTMAN** EAA (Ethyl Acetoacetate) which must meet all of the requirements listed in Section B when tested as directed by the referenced methods.
- A-3. Eastman's Material Safety Data Sheet outlines the safety precautions for **EASTMAN** EAA (Ethyl Acetoacetate).

B. PROPERTIES AND TEST METHODS

B-1.	Assay, as Ethyl Acetoacetate, %	99.00 Minimum	TEAD-A-AN-G-GC-36
B-2.	Color, pcs	15 Maximum	TEAD-A-AN-G-VCC-11
B-3.	Appearance	Clear and Free of Suspended Matter	TEAD-A-AN-G-MIS-20
B-4.	Specific Gravity @ 20/20°C	1.027 Minimum 1.032 Maximum	TEAD-A-AN-G-DEN-2
B-5.	Water, %	0.15 Maximum	TEAD-A-AN-G-VA-307
B-6.	Acidity, as Acetic Acid, %	0.20% Maximum	TEAD-A-AN-G-VA-12
B-7.	Ethyl Alcohol, %	0.20 Maximum	TEAD-A-AN-G-GC-36

EASTMAN is a trademark of Eastman Chemical Company. Copyright 2005 Eastman Chemical Company.

EASTMAN

For reasons of safety and accuracy, the person performing methods described herein must be thoroughly trained and under the supervision of a professional person who is knowledgeable in the relevant science. Equipment and materials described should be used in accordance with safety precautions recommended by their manufacturers.

Eastman Chemical Company
Kingsport, Tennessee 37662