

Technical Bulletin / Datasheet

SOLVAR E

Description : Low viscosity alkyd resin.
An overview of all products is available on request. 100% solids.

Composition : Linseed oil based.
Oil length : 74%

Application field : Wetting varnishes.
Flow additive.

Special properties and advantages : Pigment wetting.
Gloss.
Flow.
Higher water-uptake.

Recommendations :
An overview of starting point formulations is available on request.

Typical properties : Viscosity GH 25°C 10" - 14"
Test methods available on request. Acid Value (mg KOH/g) max. 12
Colour Gardner '33 max. 12
Methanol number 45 -65

Former name : Solvar

date : 01/09/2005
Replaces date : 11/08/2005

Hexion Specialty Chemicals BVBA
Ketenislaan 1c-Haven 1520, B-9130 Kalle, Belgium
Tel: +32.3.570.94.94 Fax: +32.3.570.94.90

Hexion Specialty Chemicals Inc. - USA Headquarters - 8601 95th Street - Pleasant Prairie - WI 53158
Tel: +1.262.947-7300 Fax: +1.262.947-7328

Europe, Middle East and Africa – North America – Asia Pacific

Material Safety Data Sheets providing safety precautions that should be observed in handling and storing Hexion Specialty Chemicals BVBA products are available upon request. You should obtain material safety information before handling any of these products. If any materials are mentioned that are not Hexion Specialty Chemicals BVBA products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be observed.

Neither Hexion Specialty Chemicals BVBA nor its marketing affiliates shall be responsible for the use of this information, or of any product, method, or apparatus mentioned, and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and for the safety of your employees and purchasers of your products. No warranty is made of the merchantability or fitness of any product, and nothing herein waives any of the Seller's conditions of sale.